



OMEGA SHIELDING

P R O D U C T S


We manufacture confidence.™

Catalog

Contact Series


Spherical U Contact Series

099-180-NT




NUM FINGERS	256
MIN MOUNT	0.21 (in) 5.3 (mm)
MIN GAP	0.04 (in) 1 (mm)
MAX GAP	0.07 (in) 1.8 (mm)
PITCH	0.0625 (in) 1.59 (mm)
SLOT	0.020 (in) 0.51 (mm)
FINGER	0.0425 (in) 1.08 (mm)
WIDTH	0.19 (in) 4.8 (mm)
OFFSET	0.09 (in) 2.3 (mm)
LENGTH	16.0 (in) 406.4 (mm)
THICKNESS	0.0040 (in) 0.102 (mm)

099-190-CT




NUM FINGERS	256
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.0425 (in)1.08 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0040 (in)0.102 (mm)

099-190-NT




NUM FINGERS	256
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.0425 (in)1.08 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0040 (in)0.102 (mm)

099-128-CT




NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.1 (in)2.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.20 (in)5.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0080 (in)0.203 (mm)

099-128-NT




NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.10 (in)2.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.20 (in)5.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0080 (in)0.203 (mm)

099-129-CT




NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.1 (in)2.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.20 (in)5.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0100 (in)0.254 (mm)

099-129-NT




NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.1 (in)2.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.20 (in)5.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0100 (in)0.254 (mm)

099-138-CT




NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.16 (in)4.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0080 (in)0.203 (mm)

099-138-NT




NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.08 (in)2.0 (mm)
MAX GAP	0.12 (in)3.0 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.16 (in)4.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0080 (in)0.203 (mm)

099-139-CT




NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.16 (in)4.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0100 (in)0.254 (mm)

099-139-NT




NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.16 (in)4.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0100 (in)0.254 (mm)

099-160-CT




NUM FINGERS	214
MIN MOUNT	0.29 (in)7.4 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.050 (in)1.27 (mm)
WIDTH	0.27 (in)6.9 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	16.05 (in)407.7 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-160-NT




NUM FINGERS	214
MIN MOUNT	0.29 (in)7.4 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.050 (in)1.27 (mm)
WIDTH	0.27 (in)6.9 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	16.05 (in)407.7 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-170-CT




NUM FINGERS	214
MIN MOUNT	0.29 (in)7.4 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.050 (in)1.27 (mm)
WIDTH	0.27 (in)6.9 (mm)
OFFSET	0.16 (in)4.1 (mm)
LENGTH	16.05 (in)407.7 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-170-NT




NUM FINGERS	214
MIN MOUNT	0.29 (in)7.4 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.050 (in)1.27 (mm)
WIDTH	0.27 (in)6.9 (mm)
OFFSET	0.16 (in)4.1 (mm)
LENGTH	16.05 (in)407.7 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-180-CT




NUM FINGERS	256
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.0425 (in)1.08 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0040 (in)0.102 (mm)

095-190-NT




NUM FINGERS	256
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.0425 (in)1.08 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0040 (in)0.102 (mm)

095-190-CT




NUM FINGERS	256
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.0425 (in)1.08 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0040 (in)0.102 (mm)

096-128-NT




NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.1 (in)2.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.20 (in)5.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0080 (in)0.203 (mm)

096-128-CT




NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.1 (in)2.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.20 (in)5.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0080 (in)0.203 (mm)

098-128-NT



NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.10 (in)2.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.20 (in)5.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0040 (in)0.102 (mm)


098-138-NT



NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.08 (in)2.0 (mm)
MAX GAP	0.12 (in)3.0 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.16 (in)4.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0040 (in)0.102 (mm)


Flat Contact Series

099-610-CT




NUM FINGERS	85
MIN MOUNT	0.79 (in)20.1 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.77 (in)19.6 (mm)
OFFSET	0.23 (in)5.8 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-610-NT




NUM FINGERS	85
MIN MOUNT	0.79 (in)20.1 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.77 (in)19.6 (mm)
OFFSET	0.23 (in)5.8 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-612-CT




NUM FINGERS	85
MIN MOUNT	0.91 (in)23.1 (mm)
MIN GAP	0.13 (in)3.3 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.89 (in)22.6 (mm)
OFFSET	0.13 (in)3.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-612-NT




NUM FINGERS	85
MIN MOUNT	0.91 (in)23.1 (mm)
MIN GAP	0.13 (in)3.3 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.89 (in)22.6 (mm)
OFFSET	0.13 (in)3.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-613-CT




NUM FINGERS	85
MIN MOUNT	0.94 (in)23.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.92 (in)23.4 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-613-NT




NUM FINGERS	85
MIN MOUNT	0.94 (in)23.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.92 (in)23.4 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-614-CT




NUM FINGERS	85
MIN MOUNT	0.94 (in)23.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.92 (in)23.4 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-614-NT




NUM FINGERS	85
MIN MOUNT	0.94 (in)23.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.92 (in)23.4 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-616-CT



NUM FINGERS	85
MIN MOUNT	0.91 (in)23.1 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.89 (in)22.6 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)


099-616-NT



NUM FINGERS	85
MIN MOUNT	0.91 (in)23.1 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.89 (in)22.6 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)


Spherical Flat Contact Series

099-617-CT




NUM FINGERS	85
MIN MOUNT	0.91 (in)23.1 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.89 (in)22.6 (mm)
OFFSET	0.13 (in)3.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-617-NT




NUM FINGERS	85
MIN MOUNT	0.91 (in)23.1 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.89 (in)22.6 (mm)
OFFSET	0.13 (in)3.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-618-CT




NUM FINGERS	85
MIN MOUNT	0.75 (in)19.1 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.73 (in)18.5 (mm)
OFFSET	0.13 (in)3.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-618-NT




NUM FINGERS	85
MIN MOUNT	0.75 (in)19.1 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.048 (in)1.22 (mm)
FINGER	0.140 (in)3.56 (mm)
WIDTH	0.73 (in)18.5 (mm)
OFFSET	0.13 (in)3.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-623-CT




NUM FINGERS	256
MIN MOUNT	0.36 (in)9.1 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.03 (in)0.8 (mm)
PITCH	0.0625 (in)1.6 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.0425 (in)1.09 (mm)
WIDTH	0.34 (in)8.6 (mm)
OFFSET	0.04 (in)1 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0040 (in)0.102 (mm)

099-623-NT




NUM FINGERS	256
MIN MOUNT	0.36 (in)9.1 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.03 (in)0.8 (mm)
PITCH	0.0625 (in)1.6 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.0425 (in)1.09 (mm)
WIDTH	0.34 (in)8.6 (mm)
OFFSET	0.04 (in)1 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0040 (in)0.102 (mm)

099-634-CT




NUM FINGERS	214
MIN MOUNT	0.55 (in)14 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.050 (in)1.27 (mm)
WIDTH	0.53 (in)13.5 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	16.05 (in)407.7 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-634-NT




NUM FINGERS	214
MIN MOUNT	0.55 (in)14 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.050 (in)1.27 (mm)
WIDTH	0.53 (in)13.5 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	16.05 (in)407.7 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-636-NT




NUM FINGERS	214
MIN MOUNT	0.4 (in)10.2 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.050 (in)1.27 (mm)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	16.05 (in)407.7 (mm)
THICKNESS	0.0050 (in)0.127 (mm)

099-637-CT



NUM FINGERS	170
MIN MOUNT	0.8 (in)20.3 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.78 (in)19.8 (mm)
OFFSET	0.1 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0100 (in)0.254 (mm)


099-637-NT



NUM FINGERS	170
MIN MOUNT	0.8 (in)20.3 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.78 (in)19.8 (mm)
OFFSET	0.1 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0100 (in)0.254 (mm)


U Contact Series

099-110-CT




NUM FINGERS	85
MIN MOUNT	0.5 (in)12.7 (mm)
MIN GAP	0.14 (in)3.6 (mm)
MAX GAP	0.21 (in)5.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.064 (in)1.63 (mm)
FINGER	0.124 (in)3.15 (mm)
WIDTH	0.48 (in)12.2 (mm)
OFFSET	0.28 (in)7.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0060 (in)0.152 (mm)

099-110-NT




NUM FINGERS	85
MIN MOUNT	0.5 (in)12.7 (mm)
MIN GAP	0.14 (in)3.6 (mm)
MAX GAP	0.21 (in)5.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.064 (in)1.63 (mm)
FINGER	0.124 (in)3.15 (mm)
WIDTH	0.48 (in)12.2 (mm)
OFFSET	0.28 (in)7.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0060 (in)0.152 (mm)

099-140-CT




NUM FINGERS	192
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.03 (in)0.8 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.0425 (in)1.08 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-140-NT




NUM FINGERS	192
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.03 (in)0.8 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.0425 (in)1.08 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-145-CT




NUM FINGERS	192
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.0425 (in)1.08 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-145-NT




NUM FINGERS	192
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.0425 (in)1.08 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-150-CT



NUM FINGERS	96
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.125 (in)3.18 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.105 (in)2.67 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-150-NT




NUM FINGERS	96
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.125 (in)3.18 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.105 (in)2.67 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

Fold Over Series


Enclosed Fold Over Series

099-701-NT




NUM FINGERS	64
MIN MOUNT	0.78 (in)19.8 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.17 (in)4.3 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.343 (in)8.71 (mm)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.23 (in)5.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0038 (in)0.097 (mm)

099-701-WT




NUM FINGERS	64
MIN MOUNT	0.78 (in)19.8 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.17 (in)4.3 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.343 (in)8.71 (mm)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.23 (in)5.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0038 (in)0.097 (mm)

099-721-NT




NUM FINGERS	64
MIN MOUNT	0.53 (in)13.5 (mm)
MIN GAP	0.07 (in)1.8 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
WIDTH	0.51 (in)13 (mm)
OFFSET	0.15 (in)3.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-721-WT




NUM FINGERS	64
MIN MOUNT	0.53 (in)13.5 (mm)
MIN GAP	0.07 (in)1.8 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
WIDTH	0.51 (in)13.0 (mm)
OFFSET	0.15 (in)3.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-741-NT



NUM FINGERS	85
MIN MOUNT	0.39 (in)9.9 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.32 (mm)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.12 (in)3.0 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)

099-741-WT




NUM FINGERS	85
MIN MOUNT	0.39 (in)9.9 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.32 (mm)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)

099-761-NT



NUM FINGERS	86
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.188 (in)4.76 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.3 (mm)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	16.13 (in)409.7 (mm)
THICKNESS	0.0025 (in)0.064 (mm)

099-761-WT




NUM FINGERS	86
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.188 (in)4.76 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.3 (mm)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	16.13 (in)409.7 (mm)
THICKNESS	0.0025 (in)0.064 (mm)

098-761-NT




NUM FINGERS	85
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.188 (in)4.76 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.3 (mm)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	16.13 (in)409.7 (mm)
THICKNESS	0.0022 (in)0.056 (mm)

098-761-WT




NUM FINGERS	86
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.188 (in)4.76 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.3 (mm)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	16.13 (in)409.7 (mm)
THICKNESS	0.0022 (in)0.056 (mm)

096-721-NT



NUM FINGERS	64
MIN MOUNT	0.53 (in)13.5 (mm)
MIN GAP	0.07 (in)1.8 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
WIDTH	0.51 (in)13.0 (mm)
OFFSET	0.15 (in)3.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)


096-721-WT



NUM FINGERS	64
MIN MOUNT	0.53 (in)13.5 (mm)
MIN GAP	0.07 (in)1.8 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
WIDTH	0.51 (in)13.0 (mm)
OFFSET	0.15 (in)3.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

Fold Over Clip On Series

099-702-07



NUM FINGERS	64
MIN MOUNT	0.82 (in)20.8 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.17 (in)4.3 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.343 (in)8.71 (mm)
LANCE	"V" Style (every finger / 64 per strip)
WIDTH	0.80 (in)20.3 (mm)
OFFSET	0.23 (in)5.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0038 (in)0,097 (mm)
CLIP-ON	0.07 (in)1.8 (mm)
MIN MOUNT THICKNESS	0.035-0.065 (in)0.89-1.65 (mm)


099-722-04



NUM FINGERS	64
MIN MOUNT	0.62 (in)15.7 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
LANCE	"V" Style (every finger / 64 per strip)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.15 (in)3.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)


Fold Over Sub Series

099-700-NT




NUM FINGERS	64
MIN MOUNT	0.78 (in)19.8 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.17 (in)4.3 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.343 (in)8.71 (mm)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.23 (in)5.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0038 (in)0.097 (mm)

099-700-WT




NUM FINGERS	64
MIN MOUNT	0.78 (in)19.8 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.17 (in)4.3 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.343 (in)8.71 (mm)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.23 (in)5.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0038 (in)0.097 (mm)

099-720-NT




NUM FINGERS	64
MIN MOUNT	0.53 (in)13.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-720-WT




NUM FINGERS	64
MIN MOUNT	0.53 (in)13.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-738-NT



NUM FINGERS	64
MIN MOUNT	0.95 (in)24.1 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)

099-738-WT



NUM FINGERS	64
MIN MOUNT	0.95 (in)24.1 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)

099-740-NT




NUM FINGERS	85
MIN MOUNT	0.39 (in)9.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.32 (mm)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)

099-740-WT




NUM FINGERS	85
MIN MOUNT	0.39 (in)9.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.32 (mm)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)

096-720-NT



NUM FINGERS	64
MIN MOUNT	0.53 (in)13.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

096-720-WT



NUM FINGERS	64
MIN MOUNT	0.53 (in)13.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

096-740-NT



NUM FINGERS	85
MIN MOUNT	0.39 (in)9.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.32 (mm)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)

096-740-WT



NUM FINGERS	85
MIN MOUNT	0.39 (in)9.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.32 (mm)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)

098-740-NT



NUM FINGERS	85
MIN MOUNT	0.39 (in)9.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.32 (mm)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0022 (in)0.056 (mm)

098-740-WT




NUM FINGERS	85
MIN MOUNT	0.39 (in)9.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.32 (mm)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0022 (in)0.056 (mm)

Hi Deflection Series


Hi Deflection Right Angle Series

099-320-00




NUM FINGERS	32
MIN MOUNT	1.14 (in)29 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	1.12 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
FLAT SECTION	0.19 (in)4.8 (mm)

099-330-00




NUM FINGERS	32
MIN MOUNT	1.52 (in)38.6 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	1.50 (in)38.1 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
FLAT SECTION	0.19 (in)4.8 (mm)

099-300-NT



NUM FINGERS	32
MIN MOUNT	0.95 (in)24.1 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	0.83 (in)21.3 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
FLAT SECTION	0.73 (in)18.5 (mm)


099-300-WT



NUM FINGERS	32
MIN MOUNT	0.95 (in)24.1 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	0.83 (in)21.3 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
FLAT SECTION	0.73 (in)18.5 (mm)


Hi Deflection Clip On Series

099-840-06




NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-840-08




NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-840-12




NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.12 (in)3 (mm)
MIN MOUNT THICKNESS	0.075-0.115 (in)1.91-2.92 (mm)

099-841-06




NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
LANCE	"C" Style (every 2 fingers (22 per strip)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-841-08



NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
LANCE	"C" Style (every 2 fingers / 22 per strip)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)


099-841-12



NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
LANCE	"C" Style (every 2 fingers / 22 per strip)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.12 (in)3 (mm)
MIN MOUNT THICKNESS	0.075-0.115 (in)1.91-2.92 (mm)

Hi Deflection Sub Series

099-400-00




NUM FINGERS	800
MIN MOUNT	1.12 (in)28.4 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	300 (in)7620 (mm)
THICKNESS	0.0045 (in)0.114 (mm)

Right Angle Series


Hi Deflection Right Angle Series

099-320-00




NUM FINGERS	32
MIN MOUNT	1.14 (in)29 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	1.12 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
FLAT SECTION	0.19 (in)4.8 (mm)

099-330-00




NUM FINGERS	32
MIN MOUNT	1.52 (in)38.6 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	1.50 (in)38.1 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
FLAT SECTION	0.19 (in)4.8 (mm)

099-300-NT



NUM FINGERS	32
MIN MOUNT	0.95 (in)24.1 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	0.83 (in)21.3 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
FLAT SECTION	0.73 (in)18.5 (mm)


099-300-WT



NUM FINGERS	32
MIN MOUNT	0.95 (in)24.1 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	0.83 (in)21.3 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
FLAT SECTION	0.73 (in)18.5 (mm)


Twist Right Angle Series

099-201-NT




NUM FINGERS	146
MIN MOUNT	0.11 (in)2.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.09 (in)2.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.069 (mm)
FLAT SECTION	0.25 (in)6.4 (mm)

099-201-WT




NUM FINGERS	146
MIN MOUNT	0.11 (in)2.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.09 (in)2.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
FLAT SECTION	0.25 (in)6.4 (mm)

099-211-NT




NUM FINGERS	146
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
FLAT SECTION	0.27 (in)6.9 (mm)

099-211-WT




NUM FINGERS	146
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
FLAT SECTION	0.27 (in)6.9 (mm)

099-251-NT



NUM FINGERS	250
MIN MOUNT	0.1 (in)2.5 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
WIDTH	0.08 (in)2 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
FLAT SECTION	0.18 (in)4.6 (mm)


099-251-WT



NUM FINGERS	250
MIN MOUNT	0.1 (in)2.5 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
WIDTH	0.08 (in)2 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
FLAT SECTION	0.18 (in)4.6 (mm)


Right Angle Sub Series

099-705-NT




NUM FINGERS	64
MIN MOUNT	0.78 (in)19.8 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.16 (in)4.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.032 (in)0.87 (mm)
FINGER	0.343 (in)8.71 (mm)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.21 (in)5.3 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
FLAT SECTION	0.71 (in)18.0 (mm)

099-705-WT




NUM FINGERS	64
MIN MOUNT	0.78 (in)19.8 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.16 (in)4.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.032 (in)0.87 (mm)
FINGER	0.343 (in)8.71 (mm)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.21 (in)5.3 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
FLAT SECTION	0.71 (in)18.0 (mm)

099-725-NT




NUM FINGERS	64
MIN MOUNT	0.4 (in)10.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
FLAT SECTION	0.46 (in)12.4 (mm)

099-725-WT




NUM FINGERS	64
MIN MOUNT	0.4 (in)10.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
FLAT SECTION	0.46 (in)12.4 (mm)

099-745-NT



NUM FINGERS	85
MIN MOUNT	0.3 (in)7.6 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.32 (mm)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0027 (in)0.076 (mm)
FLAT SECTION	0.35 (in)8.9 (mm)

099-745-WT




NUM FINGERS	85
MIN MOUNT	0.3 (in)7.6 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.170 (in)4.32 (mm)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
FLAT SECTION	0.35 (in)8.9 (mm)

Twist Series


Twist Right Angle Series

099-201-NT




NUM FINGERS	146
MIN MOUNT	0.11 (in)2.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.09 (in)2.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.069 (mm)
FLAT SECTION	0.25 (in)6.4 (mm)

099-201-WT




NUM FINGERS	146
MIN MOUNT	0.11 (in)2.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.09 (in)2.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
FLAT SECTION	0.25 (in)6.4 (mm)

099-211-NT




NUM FINGERS	146
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
FLAT SECTION	0.27 (in)6.9 (mm)

099-211-WT




NUM FINGERS	146
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
FLAT SECTION	0.27 (in)6.9 (mm)

099-251-NT



NUM FINGERS	250
MIN MOUNT	0.1 (in)2.5 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
WIDTH	0.08 (in)2 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
FLAT SECTION	0.18 (in)4.6 (mm)


099-251-WT



NUM FINGERS	250
MIN MOUNT	0.1 (in)2.5 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
WIDTH	0.08 (in)2 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
FLAT SECTION	0.18 (in)4.6 (mm)


Mini Twist Series

099-250-NT



NUM FINGERS	250
MIN MOUNT	0.25 (in)6.4 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
WIDTH	0.23 (in)5.8 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0030 (in)0.076 (mm)


099-250-WT



NUM FINGERS	250
MIN MOUNT	0.25 (in)6.4 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
WIDTH	0.23 (in)5.8 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0030 (in)0.076 (mm)


Dual Twist Series

099-220-NT




NUM FINGERS	146
MIN MOUNT	0.52 (in)13.2 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.5 (in)12.7 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-220-WT




NUM FINGERS	146
MIN MOUNT	0.52 (in)13.2 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.5 (in)12.7 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

095-220-NT



NUM FINGERS	146
MIN MOUNT	0.52 (in)13.2 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.6 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.50 (in)12.7 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)


095-220-WT



NUM FINGERS	146
MIN MOUNT	0.52 (in)13.2 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.50 (in)12.7 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)


Low Profile Twist Series

099-270-NT



NUM FINGERS	169
MIN MOUNT	0.38 (in)9.7 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.03 (in)0.8 (mm)
PITCH	0.095 (in)2.41 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.075 (in)1.91 (mm)
WIDTH	0.36 (in)9.1 (mm)
OFFSET	0.04 (in)1 (mm)
LENGTH	16.05 (in)407.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-270-WT



NUM FINGERS	169
MIN MOUNT	0.38 (in)9.7 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.03 (in)0.8 (mm)
PITCH	0.095 (in)2.41 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.075 (in)1.91 (mm)
WIDTH	0.36 (in)9.1 (mm)
OFFSET	0.04 (in)1 (mm)
LENGTH	16.05 (in)407.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)


Twist Clip On Series

099-203-04




NUM FINGERS	97
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-203-06




NUM FINGERS	97
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-203-08




NUM FINGERS	97
MIN MOUNT	0.19 (in)4.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.17 (in)4.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-204-04




NUM FINGERS	97
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 5 fingers / 19 per strip)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-204-06




NUM FINGERS	97
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 16 per strip)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-204-08




NUM FINGERS	97
MIN MOUNT	0.19 (in)4.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 16 per strip)
WIDTH	0.17 (in)4.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-213-04




NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-213-06




NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-213-08




NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-214-04




NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 16 per strip)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-214-06



NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 16 per strip)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)


099-214-08



NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 16 per strip)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)


Mini Twist Clip On Series

099-253-04




NUM FINGERS	167
MIN MOUNT	0.17 (in)4.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
WIDTH	0.15 (in)3.8 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	16.03 (in)407.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-253-06




NUM FINGERS	167
MIN MOUNT	0.17 (in)4.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
WIDTH	0.15 (in)3.8 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	16.03 (in)407.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-254-04



NUM FINGERS	167
MIN MOUNT	0.17 (in)4.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
LANCE	"C" Style (every 10 fingers / 17 per strip)
WIDTH	0.15 (in)3.8 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	16.03 (in)407.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)


099-254-06



NUM FINGERS	167
MIN MOUNT	0.17 (in)4.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
LANCE	"C" Style (every 10 fingers / 17 per strip)
WIDTH	0.15 (in)3.8 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	16.03 (in)407.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)


Enviro Twist Series

099-200-PT




NUM FINGERS	146
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-210-PT




NUM FINGERS	146
MIN MOUNT	0.36 (in)9.1 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.34 (in)8.6 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-220-PT



NUM FINGERS	146
MIN MOUNT	0.52 (in)13.2 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.50 (in)12.7 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)


099-270-PT



NUM FINGERS	169
MIN MOUNT	0.38 (in)9.7 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.03 (in)0.8 (mm)
PITCH	0.095 (in)2.41 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.075 (in)1.91 (mm)
WIDTH	0.36 (in)9.1 (mm)
OFFSET	0.04 (in)1 (mm)
LENGTH	16.05 (in)407.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)


Twist Sub Series

099-200-NT




NUM FINGERS	146
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-200-WT




NUM FINGERS	146
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-210-NT




NUM FINGERS	146
MIN MOUNT	0.36 (in)9.1 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.34 (in)8.6 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-210-WT




NUM FINGERS	146
MIN MOUNT	0.36 (in)9.1 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.34 (in)8.6 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

095-210-NT



NUM FINGERS	146
MIN MOUNT	0.36 (in)9.1 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.34 (in)8.6 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

095-210-WT




NUM FINGERS	146
MIN MOUNT	0.36 (in)9.1 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.34 (in)8.6 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	24.09 (in)611.9 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

Clip On Series

Transverse Clip On Series


099-490-06



NUM FINGERS	40
MIN MOUNT	0.2 (in)5.1 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.03 (in)0.8 (mm)
PITCH	0.300 (in)7.62 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.280 (in)7.11 (mm)
LANCE	"C" Style (every finger / 40 per strip)
WIDTH	0.18 (in)4.6 (mm)
OFFSET	0.04 (in)1 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)


Mini Twist Clip On Series

099-253-04




NUM FINGERS	167
MIN MOUNT	0.17 (in)4.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
WIDTH	0.15 (in)3.8 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	16.03 (in)407.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-253-06




NUM FINGERS	167
MIN MOUNT	0.17 (in)4.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
WIDTH	0.15 (in)3.8 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	16.03 (in)407.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-254-04



NUM FINGERS	167
MIN MOUNT	0.17 (in)4.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
LANCE	"C" Style (every 10 fingers / 17 per strip)
WIDTH	0.15 (in)3.8 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	16.03 (in)407.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)


099-254-06



NUM FINGERS	167
MIN MOUNT	0.17 (in)4.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.096 (in)2.44 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.081 (in)2.06 (mm)
LANCE	"C" Style (every 10 fingers / 17 per strip)
WIDTH	0.15 (in)3.8 (mm)
OFFSET	0.03 (in)0.8 (mm)
LENGTH	16.03 (in)407.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)


Twist Clip On Series

099-203-04




NUM FINGERS	97
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-203-06




NUM FINGERS	97
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-203-08




NUM FINGERS	97
MIN MOUNT	0.19 (in)4.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.17 (in)4.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-204-04




NUM FINGERS	97
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 5 fingers / 19 per strip)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-204-06




NUM FINGERS	97
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 16 per strip)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-204-08




NUM FINGERS	97
MIN MOUNT	0.19 (in)4.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 16 per strip)
WIDTH	0.17 (in)4.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-213-04




NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-213-06




NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-213-08




NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-214-04




NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 16 per strip)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-214-06



NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 16 per strip)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)


099-214-08



NUM FINGERS	97
MIN MOUNT	0.27 (in)6.9 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 16 per strip)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)


Mini Reverse Clip On Series

099-855-04




NUM FINGERS	96
MIN MOUNT	0.17 (in)4.3 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.125 (in)3.18 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.105 (in)2.67 (mm)
WIDTH	0.15 (in)3.8 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-855-06



NUM FINGERS	96
MIN MOUNT	0.17 (in)4.3 (mm)
MIN GAP	0.04 (in)1.0 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.125 (in)3.18 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.105 (in)2.67 (mm)
WIDTH	0.15 (in)3.8 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

096-855-06



NUM FINGERS	96
MIN MOUNT	0.17 (in)4.3 (mm)
MIN GAP	0.04 (in)1.0 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.125 (in)3.18 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.105 (in)2.67 (mm)
WIDTH	0.15 (in)3.8 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)


Bi Directional Clip On Series

099-440-07



NUM FINGERS	64
MIN MOUNT	0.33 (in)8.4 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.500 (in)12.7 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.210 (in)5.33 (mm)
LANCE	"C" Style (every 2 fingers / 32 per strip)
WIDTH	0.40 (in)10.2 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
FLAT SECTION	0.13 (in)3.3 (mm)
CLIP-ON	0.07 (in)1.8 (mm)
MIN MOUNT THICKNESS	0.035-0.065 (in)0.89-1.65 (mm)

099-441-07



NUM FINGERS	64
MIN MOUNT	0.33 (in)8.4 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)12.7 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.210 (in)5.33 (mm)
LANCE	"C\" Style (every 2 fingers / 32 per strip)
WIDTH	0.43 (in)10.9 (mm)
OFFSET	0.12 (in)3.0 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
FLAT SECTION	0.12 (in)3.0 (mm)
CLIP-ON	0.07 (in)1.8 (mm)
MIN MOUNT THICKNESS	0.035-0.065 (in)0.89-1.65 (mm)


096-440-07



NUM FINGERS	64
MIN MOUNT	0.33 (in)8.4 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.500 (in)12.70 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.210 (in)5.33 (mm)
LANCE	"C" Style (every 2 fingers / 32 per strip)
WIDTH	0.40 (in)10.2 (mm)
OFFSET	0.09 (in)2.3 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
FLAT SECTION	0.13 (in)3.3 (mm)
CLIP-ON	0.07 (in)1.8 (mm)
MIN MOUNT THICKNESS	0.035-0.065 (in)0.89-1.65 (mm)

Longitudinal Clip On Series


099-485-06



NUM FINGERS	40
MIN MOUNT	0.2 (in)5.1 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.03 (in)0.8 (mm)
PITCH	0.300 (in)7.62 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.280 (in)7.11 (mm)
LANCE	"C" Style (every finger / 40 per strip)
WIDTH	0.18 (in)4.6 (mm)
OFFSET	0.04 (in)1 (mm)
LENGTH	12.0 (in)304.8 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)


Mini Clip On Series

099-800-04




NUM FINGERS	73
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1.0 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	12.05 (in)306.1 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1.0 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-800-06




NUM FINGERS	73
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	12.05 (in)306.1 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-801-04




NUM FINGERS	73
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1.0 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 12 per strip)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	12.05 (in)306.1 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1.0 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-801-06




NUM FINGERS	73
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 12 per strip)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	12.05 (in)306.1 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-804-04




NUM FINGERS	73
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 2 fingers / 36 per strip)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	12.05 (in)306.1 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-802-04




NUM FINGERS	73
MIN MOUNT	0.2 (in)5.1 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.18 (in)4.6 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	12.05 (in)306.1 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-802-06




NUM FINGERS	73
MIN MOUNT	0.2 (in)5.1 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.18 (in)4.6 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	12.05 (in)306.1 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-803-04




NUM FINGERS	73
MIN MOUNT	0.2 (in)5.1 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 12 per strip)
WIDTH	0.18 (in)4.6 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	12.05 (in)306.1 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-803-06




NUM FINGERS	73
MIN MOUNT	0.2 (in)5.1 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 12 per strip)
WIDTH	0.18 (in)4.6 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	12.05 (in)306.1 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

096-800-04



NUM FINGERS	73
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1.0 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	12.05 (in)306.1 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1.0 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)


096-801-04



NUM FINGERS	73
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1.0 (mm)
PITCH	0.165 (in)4.19 (mm)
SLOT	0.015 (in)0.38 (mm)
FINGER	0.150 (in)3.81 (mm)
LANCE	"C" Style (every 6 fingers / 12 per strip)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.05 (in)1.3 (mm)
LENGTH	12.05 (in)306.1 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1.0 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)


Clip On Sub Series

099-830-04




NUM FINGERS	85
MIN MOUNT	0.47 (in)11.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.45 (in)11.4 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-830-06




NUM FINGERS	85
MIN MOUNT	0.47 (in)11.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.45 (in)11.4 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-830-08




NUM FINGERS	85
MIN MOUNT	0.47 (in)11.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.45 (in)11.4 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-831-04




NUM FINGERS	85
MIN MOUNT	0.47 (in)11.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.45 (in)11.4 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-831-06




NUM FINGERS	85
MIN MOUNT	0.47 (in)11.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.45 (in)11.4 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-831-08




NUM FINGERS	85
MIN MOUNT	0.47 (in)11.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.45 (in)11.4 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-833-05




NUM FINGERS	96
MIN MOUNT	0.47 (in)11.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.1875 (in)4.76 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.1475 (in)3.747 (mm)
LANCE	"C\" Style (every 2 fingers / 48 per strip)
WIDTH	0.45 (in)11.4 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.05 (in)1.3 (mm)
MIN MOUNT THICKNESS	0.025-0.045 (in)0.64-1.14 (mm)

099-833-07




NUM FINGERS	96
MIN MOUNT	0.47 (in)11.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.1875 (in)4.76 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.1475 (in)3.747 (mm)
LANCE	"C\" Style (every 2 fingers / 48 per strip)
WIDTH	0.45 (in)11.4 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.07 (in)1.8 (mm)
MIN MOUNT THICKNESS	0.035-0.065 (in)0.89-1.65 (mm)

099-850-04




NUM FINGERS	65
MIN MOUNT	0.58 (in)14.7 (mm)
MIN GAP	0.03 (in)0.8 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.249 (in)6.32 (mm)
SLOT	0.030 (in)0.76 (mm)
FINGER	0.219 (in)5.56 (mm)
WIDTH	0.56 (in)14.2 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.19 (in)411.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-850-06




NUM FINGERS	65
MIN MOUNT	0.58 (in)14.7 (mm)
MIN GAP	0.03 (in)0.8 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.249 (in)6.32 (mm)
SLOT	0.030 (in)0.76 (mm)
FINGER	0.219 (in)5.56 (mm)
WIDTH	0.56 (in)14.2 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.19 (in)411.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-850-08




NUM FINGERS	65
MIN MOUNT	0.58 (in)14.7 (mm)
MIN GAP	0.03 (in)0.8 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.249 (in)6.32 (mm)
SLOT	0.030 (in)0.76 (mm)
FINGER	0.219 (in)5.56 (mm)
WIDTH	0.56 (in)14.2 (mm)
OFFSET	0.07 (in)1.8 (mm)
LENGTH	16.19 (in)411.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-870-04




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-870-06




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-870-08




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-871-04




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
CLIP-ON	0.04 (in)1.0 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-871-06




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-871-08




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-872-04




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"C\C" Style (every 5 fingers / 17 per strip)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.8 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-810-04




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-810-06




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-810-08




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-811-04




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-811-06




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-811-08




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-820-04




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.08 (in)2.0 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-820-06




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.08 (in)2.0 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-820-08




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.08 (in)2.0 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-821-04




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.08 (in)2.0 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-821-06




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.08 (in)2.0 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-821-08




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1.0 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"\\V\\V" Style (every 5 fingers / 17 per strip)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.08 (in)2.0 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.08 (in)2.0 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-825-04




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-825-06




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-825-08




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-826-04




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-826-06




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-826-08




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-823-05




NUM FINGERS	96
MIN MOUNT	0.47 (in)11.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.1875 (in)4.76 (mm)
SLOT	0.04 (in)1.02 (mm)
FINGER	0.1475 (in)3.75 (mm)
LANCE	"C" Style (every 2 fingers / 48 per strip)
WIDTH	0.45 (in)11.4 (mm)
OFFSET	0.08 (in)2.0 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.05 (in)1.3 (mm)
MIN MOUNT THICKNESS	0.025-0.045 (in)0.64-1.14 (mm)

099-823-07




NUM FINGERS	96
MIN MOUNT	0.47 (in)11.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.1875 (in)4.76 (mm)
SLOT	0.04 (in)1.02 (mm)
FINGER	0.1475 (in)3.75 (mm)
LANCE	"C" Style (every 2 fingers / 48 per strip)
WIDTH	0.45 (in)11.4 (mm)
OFFSET	0.08 (in)2.0 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.07 (in)1.8 (mm)
MIN MOUNT THICKNESS	0.035-0.065 (in)0.89-1.65 (mm)

099-828-05




NUM FINGERS	96
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.1875 (in)4.76 (mm)
SLOT	0.04 (in)1.02 (mm)
FINGER	0.1475 (in)3.75 (mm)
LANCE	"C" Style (every 2 fingers / 48 per strip)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.05 (in)1.3 (mm)
MIN MOUNT THICKNESS	0.025-0.045 (in)0.64-1.14 (mm)

099-828-07




NUM FINGERS	96
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.1875 (in)4.76 (mm)
SLOT	0.04 (in)1.02 (mm)
FINGER	0.1475 (in)3.75 (mm)
LANCE	"C" Style (every 2 fingers / 48 per strip)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.14 (in)3.6 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.07 (in)1.8 (mm)
MIN MOUNT THICKNESS	0.035-0.065 (in)0.89-1.65 (mm)

099-860-04




NUM FINGERS	85
MIN MOUNT	0.62 (in)15.7 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.16 (in)4.1 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.21 (in)5.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0040 (in)0.102 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-860-06




NUM FINGERS	85
MIN MOUNT	0.62 (in)15.7 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.16 (in)4.1 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.21 (in)5.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0040 (in)0.102 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-860-08




NUM FINGERS	85
MIN MOUNT	0.62 (in)15.7 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.16 (in)4.1 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.21 (in)5.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0040 (in)0.102 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-861-04




NUM FINGERS	85
MIN MOUNT	0.62 (in)15.7 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.16 (in)4.1 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.21 (in)5.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0040 (in)0.102 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-861-06




NUM FINGERS	85
MIN MOUNT	0.62 (in)15.7 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.16 (in)4.1 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.21 (in)5.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0040 (in)0.102 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-861-08




NUM FINGERS	85
MIN MOUNT	0.62 (in)15.7 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.16 (in)4.1 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.21 (in)5.3 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0040 (in)0.102 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-866-08




NUM FINGERS	85
MIN MOUNT	0.62 (in)15.7 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.21 (in)5.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.54 (in)13.7 (mm)
OFFSET	0.28 (in)7.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0040 (in)0.102 (mm)
CLIP-ON	0.08 (in)2.0 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-874-04




NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 3 fingers / 29 per strip)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
CLIP-ON	0.04 (in)1.0 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

095-821-08




NUM FINGERS	85
MIN MOUNT	0.44 (in)11.2 (mm)
MIN GAP	0.04 (in)1.0 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.42 (in)10.7 (mm)
OFFSET	0.08 (in)2.0 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.08 (in)2.0 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

095-831-06



NUM FINGERS	85
MIN MOUNT	0.47 (in)11.9 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.45 (in)11.4 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)


096-871-04



NUM FINGERS	85
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2.0 (mm)
PITCH	0.188 (in)4.77 (mm)
SLOT	0.047 (in)1.19 (mm)
FINGER	0.141 (in)3.58 (mm)
LANCE	"V" Style (every 5 fingers / 17 per strip)
WIDTH	0.30 (in)7.6 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
CLIP-ON	0.04 (in)1.0 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)


Low Profile Clip On Series

099-880-04




NUM FINGERS	96
MIN MOUNT	0.27 (in)6.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.030 (in)0.76 (mm)
FINGER	0.220 (in)5.59 (mm)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)0.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-881-04




NUM FINGERS	96
MIN MOUNT	0.27 (in)6.8 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.02 (in)0.5 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.030 (in)0.76 (mm)
FINGER	0.220 (in)5.59 (mm)
LANCE	"C" Style (every 4 fingers / 24 per strip)
WIDTH	0.25 (in)6.4 (mm)
OFFSET	0.07 (in)0.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-885-04




NUM FINGERS	64
MIN MOUNT	0.3 (in)7.6 (mm)
MIN GAP	0.03 (in)0.8 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.030 (in)0.76 (mm)
FINGER	0.220 (in)5.59 (mm)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.10 (in)1.5 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.04 (in)1.0 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-886-04




NUM FINGERS	64
MIN MOUNT	0.3 (in)7.6 (mm)
MIN GAP	0.03 (in)0.8 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.030 (in)0.76 (mm)
FINGER	0.220 (in)5.59 (mm)
LANCE	"C" Style (every 4 fingers / 24 per strip)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.10 (in)1.5 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.04 (in)1.0 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

098-885-04



NUM FINGERS	64
MIN MOUNT	0.3 (in)7.6 (mm)
MIN GAP	0.03 (in)0.8 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.030 (in)0.76 (mm)
FINGER	0.220 (in)5.59 (mm)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.10 (in)1.5 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1.0 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)


098-886-04



NUM FINGERS	64
MIN MOUNT	0.3 (in)7.6 (mm)
MIN GAP	0.03 (in)0.8 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.030 (in)0.76 (mm)
FINGER	0.220 (in)5.59 (mm)
LANCE	"C" Style (every 4 fingers / 24 per strip)
WIDTH	0.28 (in)7.1 (mm)
OFFSET	0.10 (in)1.5 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1.0 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)


Fold Over Clip On Series

099-702-07



NUM FINGERS	64
MIN MOUNT	0.82 (in)20.8 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.17 (in)4.3 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.343 (in)8.71 (mm)
LANCE	"V" Style (every finger / 64 per strip)
WIDTH	0.80 (in)20.3 (mm)
OFFSET	0.23 (in)5.8 (mm)
LENGTH	24.0 (in)609.6 (mm)
THICKNESS	0.0038 (in)0.097 (mm)
CLIP-ON	0.07 (in)1.8 (mm)
MIN MOUNT THICKNESS	0.035-0.065 (in)0.89-1.65 (mm)


099-722-04



NUM FINGERS	64
MIN MOUNT	0.62 (in)15.7 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.11 (in)2.8 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.022 (in)0.56 (mm)
FINGER	0.228 (in)5.79 (mm)
LANCE	"V" Style (every finger / 64 per strip)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.15 (in)3.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)


Reverse Clip On Series

099-805-07




NUM FINGERS	64
MIN MOUNT	0.4 (in)10.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.500 (in)12.7 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.210 (in)5.33 (mm)
LANCE	"C" Style (every 2 fingers / 32 per strip)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.20 (in)5.1 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.07 (in)1.8 (mm)
MIN MOUNT THICKNESS	0.035-0.065 (in)0.89-1.65 (mm)

099-806-07




NUM FINGERS	64
MIN MOUNT	0.4 (in)10.2 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.23 (in)5.8 (mm)
PITCH	0.500 (in)12.7 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.210 (in)5.33 (mm)
LANCE	"C\" Style (every 2 fingers / 32 per strip)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.31 (in)7.9 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.07 (in)1.8 (mm)
MIN MOUNT THICKNESS	0.035-0.065 (in)0.89-1.65 (mm)

099-807-07




NUM FINGERS	64
MIN MOUNT	0.4 (in)10.2 (mm)
MIN GAP	0.07 (in)1.8 (mm)
MAX GAP	0.21 (in)5.3 (mm)
PITCH	0.500 (in)12.7 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.210 (in)5.33 (mm)
LANCE	"C" Style (every 2 fingers / 32 per strip)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.28 (in)7.1 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.07 (in)1.8 (mm)
MIN MOUNT THICKNESS	0.035-0.065 (in)0.89-1.65 (mm)

099-815-04




NUM FINGERS	85
MIN MOUNT	0.51 (in)13 (mm)
MIN GAP	0.14 (in)3.6 (mm)
MAX GAP	0.21 (in)5.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.064 (in)1.63 (mm)
FINGER	0.124 (in)3.15 (mm)
WIDTH	0.49 (in)12.4 (mm)
OFFSET	0.28 (in)7.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0060 (in)0.152 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-815-06




NUM FINGERS	85
MIN MOUNT	0.51 (in)13 (mm)
MIN GAP	0.14 (in)3.6 (mm)
MAX GAP	0.21 (in)5.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.064 (in)1.63 (mm)
FINGER	0.124 (in)3.15 (mm)
WIDTH	0.49 (in)12.4 (mm)
OFFSET	0.28 (in)7.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0060 (in)0.152 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-815-08




NUM FINGERS	85
MIN MOUNT	0.51 (in)13 (mm)
MIN GAP	0.14 (in)3.6 (mm)
MAX GAP	0.21 (in)5.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.064 (in)1.63 (mm)
FINGER	0.124 (in)3.15 (mm)
WIDTH	0.49 (in)12.4 (mm)
OFFSET	0.28 (in)7.1 (mm)
LENGTH	15.98 (in)405.9 (mm)
THICKNESS	0.0060 (in)0.152 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-816-04




NUM FINGERS	85
MIN MOUNT	0.51 (in)13 (mm)
MIN GAP	0.14 (in)3.6 (mm)
MAX GAP	0.21 (in)5.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.064 (in)1.63 (mm)
FINGER	0.124 (in)3.15 (mm)
LANCE	"C\ Style (every 3 fingers / 29 per strip)
WIDTH	0.49 (in)12.4 (mm)
OFFSET	0.28 (in)7.1 (mm)
LENGTH	16.356 (in)405.9 (mm)
THICKNESS	0.0060 (in)0.152 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-816-06



NUM FINGERS	85
MIN MOUNT	0.51 (in)13 (mm)
MIN GAP	0.14 (in)3.6 (mm)
MAX GAP	0.21 (in)5.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.064 (in)1.63 (mm)
FINGER	0.124 (in)3.15 (mm)
LANCE	"C" Style (every 3 fingers / 29 per strip)
WIDTH	0.49 (in)12.4 (mm)
OFFSET	0.28 (in)7.1 (mm)
LENGTH	16.356 (in)405.9 (mm)
THICKNESS	0.0060 (in)0.152 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)


099-816-08



NUM FINGERS	85
MIN MOUNT	0.51 (in)13 (mm)
MIN GAP	0.14 (in)3.6 (mm)
MAX GAP	0.21 (in)5.3 (mm)
PITCH	0.188 (in)4.78 (mm)
SLOT	0.064 (in)1.63 (mm)
FINGER	0.124 (in)3.15 (mm)
LANCE	"C" Style (every 3 fingers / 29 per strip)
WIDTH	0.49 (in)12.4 (mm)
OFFSET	0.28 (in)7.1 (mm)
LENGTH	16.356 (in)405.9 (mm)
THICKNESS	0.0060 (in)0.152 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)


Reverse Spherical Clip On Series

099-875-04




NUM FINGERS	224
MIN MOUNT	0.38 (in)9.7 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.050 (in)1.27 (mm)
WIDTH	0.36 (in)9.1 (mm)
OFFSET	0.16 (in)4.1 (mm)
LENGTH	16.8 (in)426.7 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-875-06




NUM FINGERS	224
MIN MOUNT	0.38 (in)9.7 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.050 (in)1.27 (mm)
WIDTH	0.36 (in)9.1 (mm)
OFFSET	0.16 (in)4.1 (mm)
LENGTH	16.8 (in)426.7 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-875-08




NUM FINGERS	224
MIN MOUNT	0.38 (in)9.7 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.050 (in)1.27 (mm)
WIDTH	0.36 (in)9.1 (mm)
OFFSET	0.16 (in)4.1 (mm)
LENGTH	16.8 (in)426.7 (mm)
THICKNESS	0.0050 (in)0.127 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-895-04



NUM FINGERS	256
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.0625 (in)1.588 (mm)
SLOT	0.020 (in)0.508 (mm)
FINGER	0.0425 (in)1.08 (mm)
WIDTH	0.24 (in)6.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)


099-895-06



NUM FINGERS	256
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.0625 (in)1.588 (mm)
SLOT	0.020 (in)0.508 (mm)
FINGER	0.0425 (in)1.08 (mm)
WIDTH	0.24 (in)6.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)


Hi Deflection Clip On Series

099-840-06




NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-840-08




NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-840-12




NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.12 (in)3 (mm)
MIN MOUNT THICKNESS	0.075-0.115 (in)1.91-2.92 (mm)

099-841-06




NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
LANCE	"C" Style (every 2 fingers (22 per strip)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-841-08



NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
LANCE	"C" Style (every 2 fingers / 22 per strip)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)


099-841-12



NUM FINGERS	43
MIN MOUNT	1.28 (in)32.5 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.2 (in)5.1 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.040 (in)1.02 (mm)
FINGER	0.335 (in)8.51 (mm)
LANCE	"C" Style (every 2 fingers / 22 per strip)
WIDTH	1.1 (in)27.9 (mm)
OFFSET	0.26 (in)6.6 (mm)
LENGTH	16.13 (in)409.6 (mm)
THICKNESS	0.0045 (in)0.114 (mm)
CLIP-ON	0.12 (in)3 (mm)
MIN MOUNT THICKNESS	0.075-0.115 (in)1.91-2.92 (mm)


No Snag Clip On Series

099-936-06




NUM FINGERS	96
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.375 (in)4.763 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.1675 (in)4.255 (mm)
LANCE	"C" Style (every 2 fingers / 48 per strip)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-945-04




NUM FINGERS	72
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-945-06




NUM FINGERS	72
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-945-08




NUM FINGERS	72
MIN MOUNT	0.15 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-946-04




NUM FINGERS	72
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
LANCE	"C" Style (every 2 fingers / 36 per strip)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-946-06




NUM FINGERS	72
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
LANCE	"C" Style (every 2 fingers / 36 per strip)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-946-08




NUM FINGERS	72
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
LANCE	"C" Style (every 2 fingers / 36 per strip)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-966-06




NUM FINGERS	48
MIN MOUNT	0.9 (in)22.9 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.18 (in)4.6 (mm)
PITCH	0.750 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
LANCE	"C" Style (every 2 fingers / 24 per strip)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-965-08




NUM FINGERS	48
MIN MOUNT	0.9 (in)22.9 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.18 (in)4.6 (mm)
PITCH	0.750 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-966-08



NUM FINGERS	48
MIN MOUNT	0.9 (in)22.9 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.18 (in)4.6 (mm)
PITCH	0.750 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
LANCE	"C" Style (every 2 fingers / 24 per strip)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-966-12




NUM FINGERS	48
MIN MOUNT	0.9 (in)22.9 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.18 (in)4.6 (mm)
PITCH	0.750 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
LANCE	"C" Style (every 2 fingers / 24 per strip)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.12 (in)3 (mm)
MIN MOUNT THICKNESS	0.075-0.115 (in)1.91-2.92 (mm)

No Snag Series


No Snag Clip On Series

099-936-06




NUM FINGERS	96
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.375 (in)4.763 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.1675 (in)4.255 (mm)
LANCE	"C" Style (every 2 fingers / 48 per strip)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-945-04




NUM FINGERS	72
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-945-06




NUM FINGERS	72
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-945-08




NUM FINGERS	72
MIN MOUNT	0.15 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-946-04




NUM FINGERS	72
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
LANCE	"C" Style (every 2 fingers / 36 per strip)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.04 (in)1 (mm)
MIN MOUNT THICKNESS	0.020-0.035 (in)0.51-0.89 (mm)

099-946-06




NUM FINGERS	72
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
LANCE	"C" Style (every 2 fingers / 36 per strip)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-946-08




NUM FINGERS	72
MIN MOUNT	0.48 (in)12.2 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.500 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
LANCE	"C" Style (every 2 fingers / 36 per strip)
WIDTH	0.46 (in)11.7 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-966-06




NUM FINGERS	48
MIN MOUNT	0.9 (in)22.9 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.18 (in)4.6 (mm)
PITCH	0.750 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
LANCE	"C" Style (every 2 fingers / 24 per strip)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.06 (in)1.5 (mm)
MIN MOUNT THICKNESS	0.035-0.055 (in)0.89-1.40 (mm)

099-965-08




NUM FINGERS	48
MIN MOUNT	0.9 (in)22.9 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.18 (in)4.6 (mm)
PITCH	0.750 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-966-08



NUM FINGERS	48
MIN MOUNT	0.9 (in)22.9 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.18 (in)4.6 (mm)
PITCH	0.750 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
LANCE	"C" Style (every 2 fingers / 24 per strip)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.08 (in)2 (mm)
MIN MOUNT THICKNESS	0.055-0.075 (in)1.40-1.91 (mm)

099-966-12



NUM FINGERS	48
MIN MOUNT	0.9 (in)22.9 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.18 (in)4.6 (mm)
PITCH	0.750 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
LANCE	"C" Style (every 2 fingers / 24 per strip)
WIDTH	0.76 (in)19.3 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
CLIP-ON	0.12 (in)3 (mm)
MIN MOUNT THICKNESS	0.075-0.115 (in)1.91-2.92 (mm)

No Snag Variable Slot Mount Series

098-934-01




NUM FINGERS	96
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.187 (in)4.75 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.169 (in)4.29 (mm)
TRIMMED FINGER TIPS	1 OUT OF EVERY 2
WIDTH	0.32 (in)8.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	17.95 (in)455.9 (mm)
THICKNESS	0.0022 (in)0.056 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0,8-1,0 (mm)

098-934-03



NUM FINGERS	96
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.187 (in)4.75 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.169 (in)4.29 (mm)
TRIMMED FINGER TIPS	3 OUT OF EVERY 4
WIDTH	0.32 (in)8.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	17.95 (in)455.9 (mm)
THICKNESS	0.0022 (in)0.056 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0,8-1,0 (mm)

098-934-05



NUM FINGERS	96
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.187 (in)4.75 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.169 (in)4.29 (mm)
TRIMMED FINGER TIPS	5 OUT OF EVERY 6
WIDTH	0.32 (in)8.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	17.95 (in)455.9 (mm)
THICKNESS	0.0022 (in)0.056 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0,8-1,0 (mm)

099-934-01




NUM FINGERS	96
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.187 (in)4.75 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.169 (in)4.29 (mm)
TRIMMED FINGER TIPS	1 OUT OF EVERY 2
WIDTH	0.32 (in)8.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	17.95 (in)455.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0,8-1,0 (mm)

099-934-03



NUM FINGERS	96
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.187 (in)4.75 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.169 (in)4.29 (mm)
TRIMMED FINGER TIPS	3 OUT OF EVERY 4
WIDTH	0.32 (in)8.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	17.95 (in)455.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0,8-1,0 (mm)

099-934-05



NUM FINGERS	96
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.187 (in)4.75 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.169 (in)4.29 (mm)
TRIMMED FINGER TIPS	5 OUT OF EVERY 6
WIDTH	0.32 (in)8.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	17.95 (in)455.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0,8-1,0 (mm)

096-934-01



NUM FINGERS	96
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.187 (in)4.75 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.169 (in)4.29 (mm)
TRIMMED FINGER TIPS	1 OUT OF EVERY 2
WIDTH	0.32 (in)8.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	17.95 (in)455.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0.8-1.0 (mm)

No Snag Sub Series

099-930-NT



NUM FINGERS	96
MIN MOUNT	0.35 (in)8.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.1875 (in)4.76 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.1675 (in)4.25 (mm)
WIDTH	0.31 (in)7.9 (mm)
OFFSET	0.12 (in)3.0 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)

099-930-WT



NUM FINGERS	96
MIN MOUNT	0.35 (in)8.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.1875 (in)4.76 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.1675 (in)4.25 (mm)
WIDTH	0.31 (in)7.9 (mm)
OFFSET	0.12 (in)3 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)

099-932-NT



NUM FINGERS	96
MIN MOUNT	0.35 (in)8.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.1875 (in)4.76 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.1675 (in)4.25 (mm)
WIDTH	0.33 (in)8.4 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-932-WT



NUM FINGERS	96
MIN MOUNT	0.35 (in)8.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.1875 (in)4.76 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.1675 (in)4.25 (mm)
WIDTH	0.33 (in)8.4 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	18 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-940-NT



NUM FINGERS	72
MIN MOUNT	0.35 (in)8.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
WIDTH	0.31 (in)7.9 (mm)
OFFSET	0.12 (in)3.0 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)

099-940-WT



NUM FINGERS	72
MIN MOUNT	0.35 (in)8.9 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.09 (in)2.3 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
WIDTH	0.31 (in)7.9 (mm)
OFFSET	0.12 (in)3.0 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)

099-960-NT




NUM FINGERS	48
MIN MOUNT	0.76 (in)19.3 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
WIDTH	0.61 (in)15.5 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

099-960-WT




NUM FINGERS	48
MIN MOUNT	0.76 (in)19.3 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
WIDTH	0.61 (in)15.5 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

089-993-NT



NUM FINGERS	
MIN MOUNT	0.60 (in)15.2 (mm)
MIN GAP	0.04 (in)1.0 (mm)
MAX GAP	0.10 (in)2.5 (mm)
PITCH	0.125 (in)3.18 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.100 (in)2.54 (mm)
WIDTH	0.60 (in)15.2 (mm)
OFFSET	0.12 (in)3.0 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0035 (in)0.089 (mm)

089-994-NT



NUM FINGERS	
MIN MOUNT	0.55 (in)14.0 (mm)
MIN GAP	0.04 (in)1.0 (mm)
MAX GAP	0.12 (in)3.0 (mm)
PITCH	0.125 (in)3.18 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.100 (in)2.54 (mm)
WIDTH	0.55 (in)14.0 (mm)
OFFSET	0.15 (in)3.8 (mm)
LENGTH	16.0 (in)406.4 (mm)
THICKNESS	0.0035 (in)0.089 (mm)

095-960-NT



NUM FINGERS	48
MIN MOUNT	0.76 (in)19.3 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
WIDTH	0.61 (in)15.5 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)


095-960-WT



NUM FINGERS	48
MIN MOUNT	0.76 (in)19.3 (mm)
MIN GAP	0.06 (in)1.5 (mm)
MAX GAP	0.19 (in)4.8 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
WIDTH	0.61 (in)15.5 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)

No Snag Slot Mount Series

099-903-00




NUM FINGERS	96
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.1875 (in)4.763 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.1675 (in)4.255 (mm)
WIDTH	0.31 (in)7.9 (mm)
OFFSET	0.12 (in)3.0 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0,8-1,0 (mm)

099-904-00



NUM FINGERS	72
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
WIDTH	0.31 (in)7.9 (mm)
OFFSET	0.12 (in)3.0 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0,8-1,0 (mm)

099-906-00



NUM FINGERS	48
MIN MOUNT	0.52 (in)13.2 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.14 (in)3.6 (mm)
PITCH	0.375 (in)9.53 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.355 (in)9.02 (mm)
WIDTH	0.62 (in)15.7 (mm)
OFFSET	0.25 (in)6.4 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0030 (in)0.076 (mm)
MIN MOUNT THICKNESS	0.06-0.07 (in)1,5-1,8 (mm)

098-931-00




NUM FINGERS	96
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.187 (in)4.75 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.169 (in)4.29 (mm)
WIDTH	0.32 (in)8.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	17.95 (in)455.9 (mm)
THICKNESS	0.0022 (in)0.056 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0,8-1,0 (mm)

099-931-00



NUM FINGERS	96
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.187 (in)4.75 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.169 (in)4.29 (mm)
WIDTH	0.32 (in)8.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	17.95 (in)455.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
MIN MOUNT	0.03-0.04 (in)0,8-1,0 (mm)
THICKNESS	

089-933-00



NUM FINGERS	96
MIN MOUNT	0.32 (in)8.1 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.187 (in)4.75 (mm)
SLOT	0.021 (in)0.53 (mm)
FINGER	0.166 (in)4.22 (mm)
WIDTH	0.32 (in)8.1 (mm)
OFFSET	0.10 (in)2.5 (mm)
LENGTH	17.95 (in)455.9 (mm)
THICKNESS	0.0020 (in)0.05 (mm)
MIN MOUNT	0.03-0.04 (in)0,8-1,0 (mm)
THICKNESS	

096-904-00



NUM FINGERS	72
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.250 (in)6.35 (mm)
SLOT	0.020 (in)0.51 (mm)
FINGER	0.230 (in)5.84 (mm)
WIDTH	0.31 (in)7.9 (mm)
OFFSET	0.12 (in)3.0 (mm)
LENGTH	18.0 (in)457.2 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0.8-1.0 (mm)

096-931-00




NUM FINGERS	96
MIN MOUNT	0.26 (in)6.6 (mm)
MIN GAP	0.01 (in)0.3 (mm)
MAX GAP	0.06 (in)1.5 (mm)
PITCH	0.187 (in)4.75 (mm)
SLOT	0.018 (in)0.46 (mm)
FINGER	0.169 (in)4.29 (mm)
WIDTH	0.32 (in)8.1 (mm)
OFFSET	0.11 (in)2.8 (mm)
LENGTH	17.95 (in)455.9 (mm)
THICKNESS	0.0027 (in)0.069 (mm)
MIN MOUNT THICKNESS	0.03-0.04 (in)0.8-1.0 (mm)

Contact Ring Series

Male Contact Ring Series

099-523-00



NUM FINGERS	256
MIN MOUNT	0.36 (in)9.1 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.03 (in)0.8 (mm)
PITCH	0.063 (in)1.6 (mm)
SLOT	0.02 (in)0.51 (mm)
FINGER	0.043 (in)1.09 (mm)
WIDTH	0.34 (in)8.6 (mm)
OFFSET	0.04 (in)1.0 (mm)
THICKNESS	0.004 (in)0.102 (mm)

099-528-00




NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.1 (in)2.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.20 (in)5.1 (mm)
THICKNESS	0.008 (in)0.203 (mm)

099-529-00



NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.1 (in)2.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.20 (in)5.1 (mm)
THICKNESS	0.01 (in)0.254 (mm)

099-534-00



NUM FINGERS	214
MIN MOUNT	0.55 (in)14 (mm)
MIN GAP	0.02 (in)0.3 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.05 (in)1.57 (mm)
WIDTH	0.53 (in)13.5 (mm)
OFFSET	0.05 (in)1.3 (mm)
THICKNESS	0.005 (in)0.127 (mm)

099-536-00



NUM FINGERS	214
MIN MOUNT	0.4 (in)10.2 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.05 (in)1.57 (mm)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.05 (in)1.3 (mm)
THICKNESS	0.005 (in)0.127 (mm)

099-537-00



NUM FINGERS	170
MIN MOUNT	0.8 (in)20.3 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.78 (in)19.8 (mm)
OFFSET	0.10 (in)2.5 (mm)
THICKNESS	0.01 (in)0.254 (mm)

099-538-00



NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.16 (in)4.1 (mm)
THICKNESS	0.008 (in)0.203 (mm)

099-539-00



NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.16 (in)4.1 (mm)
THICKNESS	0.01 (in)0.254 (mm)


Female Contact Ring Series

099-504-00



NUM FINGERS	192
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.03 (in)0.8 (mm)
MAX GAP	0.05 (in)1.3 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.02 (in)0.51 (mm)
FINGER	0.043 (in)1.08 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.07 (in)1.8 (mm)
THICKNESS	0.003 (in)0.076 (mm)

099-505-00



NUM FINGERS	96
MIN MOUNT	0.15 (in)3.8 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.125 (in)3.18 (mm)
SLOT	0.02 (in)0.51 (mm)
FINGER	0.105 (in)2.67 (mm)
WIDTH	0.13 (in)3.3 (mm)
OFFSET	0.09 (in)2.3 (mm)
THICKNESS	0.003 (in)0.076 (mm)

099-506-00



NUM FINGERS	214
MIN MOUNT	0.29 (in)7.4 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.05 (in)1.27 (mm)
WIDTH	0.27 (in)6.9 (mm)
OFFSET	0.11 (in)2.8 (mm)
THICKNESS	0.005 (in)0.127 (mm)

099-507-00



NUM FINGERS	214
MIN MOUNT	0.29 (in)7.4 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.05 (in)1.27 (mm)
WIDTH	0.27 (in)6.9 (mm)
OFFSET	0.16 (in)4.1 (mm)
THICKNESS	0.005 (in)0.127 (mm)

099-508-00



NUM FINGERS	256
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.04 (in)1 (mm)
MAX GAP	0.07 (in)1.8 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.02 (in)0.51 (mm)
FINGER	0.043 (in)1.09 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.09 (in)2.3 (mm)
THICKNESS	0.004 (in)0.102 (mm)

099-509-00



NUM FINGERS	256
MIN MOUNT	0.21 (in)5.3 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.0625 (in)1.59 (mm)
SLOT	0.02 (in)0.51 (mm)
FINGER	0.043 (in)1.09 (mm)
WIDTH	0.19 (in)4.8 (mm)
OFFSET	0.11 (in)2.8 (mm)
THICKNESS	0.004 (in)0.102 (mm)

099-532-00




NUM FINGERS	256
MIN MOUNT	0.36 (in)9.1 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.03 (in)0.8 (mm)
PITCH	0.0625 (in)1.6 (mm)
SLOT	0.02 (in)0.51 (mm)
FINGER	0.043 (in)1.09 (mm)
WIDTH	0.34 (in)8.6 (mm)
OFFSET	0.04 (in)1.0 (mm)
THICKNESS	0.004 (in)0.102 (mm)

099-543-00




NUM FINGERS	214
MIN MOUNT	0.55 (in)14 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.05 (in)1.27 (mm)
WIDTH	0.53 (in)13.5 (mm)
OFFSET	0.05 (in)1.3 (mm)
THICKNESS	0.005 (in)0.127 (mm)

099-563-00



NUM FINGERS	214
MIN MOUNT	0.4 (in)10.2 (mm)
MIN GAP	0.02 (in)0.5 (mm)
MAX GAP	0.04 (in)1 (mm)
PITCH	0.075 (in)1.91 (mm)
SLOT	0.025 (in)0.64 (mm)
FINGER	0.05 (in)1.27 (mm)
WIDTH	0.38 (in)9.7 (mm)
OFFSET	0.05 (in)1.3 (mm)
THICKNESS	0.005 (in)0.127 (mm)

099-573-00



NUM FINGERS	170
MIN MOUNT	0.8 (in)20.3 (mm)
MIN GAP	0.05 (in)1.3 (mm)
MAX GAP	0.08 (in)2 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.78 (in)19.8 (mm)
OFFSET	0.1 (in)2.5 (mm)
THICKNESS	0.01 (in)0.254 (mm)

099-582-00



NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.1 (in)2.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.20 (in)5.1 (mm)
THICKNESS	0.008 (in)0.203 (mm)

099-583-00



NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.16 (in)4.1 (mm)
THICKNESS	0.008 (in)0.203 (mm)

099-592-00



NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.1 (in)2.5 (mm)
MAX GAP	0.15 (in)3.8 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.20 (in)5.1 (mm)
THICKNESS	0.01 (in)0.254 (mm)

099-593-00



NUM FINGERS	170
MIN MOUNT	0.46 (in)11.7 (mm)
MIN GAP	0.08 (in)2 (mm)
MAX GAP	0.12 (in)3 (mm)
PITCH	0.094 (in)2.39 (mm)
SLOT	0.032 (in)0.81 (mm)
FINGER	0.062 (in)1.57 (mm)
WIDTH	0.44 (in)11.2 (mm)
OFFSET	0.16 (in)4.1 (mm)
THICKNESS	0.01 (in)0.254 (mm)

CL-Electronics GmbH
Furtbachstrasse 4, 8107 Buchs/ZH
Phone: +41 44 857 12 00
Fax: +41 44 857 12 01
Mail: sales@cl-electronics.com
Web: www.cl-electronics.com